

## VoIP phone snom 370

The Next Generation of VoIP Phones



- Tilttable, high-definition graphical display (240 x 128 Pixel)
- Large LED (red) for incoming calls
- 47 keys, 13 LEDs
- 12 programmable function keys
- Speakerphone
- Dual Ethernet connection
- Power over Ethernet
- Multiple audio device support
- Additional keypad with 42 programmable function keys
- SIP RFC3261
- Security: SIPS/SRTP, TLS
- STUN, ENUM, NAT, ICE
- Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (Full rate)
- National Language Support

### → Usability

The snom 370 is the VoIP phone for the business user who needs immediate access to all of their important information. With the large graphical, high-definition display, the snom 370 offers an improved and extended presentation of call lists, address books and caller information. Caller information can be customized easily through XML to depict the information the user wants displayed.

Through the mini browser, users can have direct access to their own applications via the display screen. Users can not only customize the design of the display but, also view news tickers and other information as well as access central or public phone directories.

### → Security

The large LED (red) announces incoming calls.

**More flexibility and productivity for your everyday work life.** The improved interface guarantees ease of use and comfort. Context-sensitive menus offer additional options according to individual requirements. The snom 370 supports several audio devices simultaneously, for example, it is possible to use the handset, headset, and loudspeaker concurrently.

**More performance through expanded memory.** The snom 370 offers more additional customer-oriented functionalities and applications. The expanded memory capacity enables the depiction of graphics and high re-

### → Interoperability

solution pictures to show the status of contacts (e.g., busy, on-line, off-line) similar to Instant Messenger. It is also possible to play music and media files and to integrate applications like VPN for increased security.

**Afraid of unwanted listeners, data theft or spam calls?** To avoid problems with unwanted violations of your audio data, the snom 370 supports the security standards TLS (Transport Layer Security), SRTP, and SIPS which are necessary to protect against electronic eavesdropping and data theft.

# Technical Data snom 370

## GENERAL FEATURES

- **Dimensions:**  
approx. 25x20x13.5 cm
- **Weight:** approx. 1000 g
- **Safety:** IEC 60950-1:2001, CB Test Certificate
- **Certifications:** FCC Class B, CE Mark
- **Power consumption:**  
2.6 – 2.8 watts

## CONNECTORS

- **1 x LAN, 1 x PC:**  
RJ45 (Ethernet)
- **Power:** 5 V DC
- **2 port Ethernet switch:**  
IEEE 802.3 10/100 Mbps
- **Power over Ethernet:**  
IEEE 802.3af, Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector
- **Expansion Module:**  
Proprietary snom connector

## USER INTERFACE

- 240 x 128 pixels, grayscale graphical display
- 47 keys; 12 programmable function keys with LEDs (54 with the expansion module)
- Call indication LED
- Caller-ID  
(with picture display)
- Message waiting indication LED
- Last calls (100 entries)
- Call list (100 entries)
- Address book (100 entries)
- Address book import/export
- Speed dialing, local dial plan
- Number guessing
- Missed calls, dialed calls, answered calls
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Handling of 12 simultaneous calls

- Menu-driven user interface
- Import of individual ring tones
- URL Dialing support
- National language support for selected languages (NLS)
- Do not disturb
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

## CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music-on-hold support (only via PBX)
- Divert
- Conferencing (3-way conference bridge on phone)
- Call park, call pickup (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Toggling
- Transfer
- Redialing
- RTP multicast paging
- Multiple audio device support

## WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone, remote configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging, syslog)

## SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP
- VLAN (802.1 pq)

## CODECS

- G.711 A-law,  $\mu$ -law
- G.729A, G.723.1, G.726
- GSM 6.10 (full rate)
- G.722

## SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/Basic authentication
- Loose routing and strict routing support
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses (RFC3262)
- Early media support
- DNS SRV (RFC3263), redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication (RFC3842), subscription for MWI events (RFC3265)
- Dialog-state monitoring
- In-band DTMF/out-of-band DTMF/ SIP INFO DTMF
- STUN client (NAT traversal)
- ENUM (RFC3261), NAPTR (RFC2915), rport (RFC3581), REFER (RFC3515)
- Event list subscription support (RFC4662)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Presence/buddy-list feature
- Busy lamp field support (BLF)
- Presence publishing

## INSTALLATION

- Automatic software update
- Automatic settings retrieval via HTTP/HTTPS/TFTP
- Installation via web interface
- Static IP provisioning, DHCP
- NTP

For more information, contact your snom partner.

snom technology AG  
Gradestraße 46  
D-12347 Berlin  
tel/enum: +49 30 39833-0  
fax: +49 30 39833-111  
sip: info@snom.com  
mail: info@snom.com