

- Compatible with VXI (Passport-V) or GN Netcom (Passport-G) lower quick disconnect cords.
- Two-year unconditional warranty.
- Sturdy quick disconnect allows fast and easy detachment from lower cord for greater mobility.



- Stainless steel, ratchet style headband secures positional adjustment, won't slide out of place.
- Noise-canceling microphone effectively reduces background noise for a more professional sounding call.

TECHNICAL SPECIFICATIONS

TRANSMIT SPECIFICATIONS

Microphone: Noise canceling electret
Ambient noise suppression: 13db @ 1kHz, typical
Output impedance: 1.8k Ohms typical
Sensitivity: -44dB @ 1kHz (defined 1" from talk-side, 82dB SPL)
Frequency response: 20Hz to 15 kHz.
Operating Current: 320 mA max.
Operating Voltage: DC 1.0V min. to 20V max.

RECEIVE SPECIFICATIONS

Speaker: Dynamic; 36mm diameter
SPL: 90db @ 1kHz, 0.55V input
Impedance: 300 Ohms
Frequency response: 200Hz to 5 kHz
Rated input: 10mW continuous, 100mW peak

MECHANICAL SPECIFICATIONS

Cables: Standard wire, PVC insulation, polyurethane jacket
Connectors: Gold-plated; quick disconnect
Microphone boom: Flexible with positioning memory; swivels 300 degrees; left or right ear placement
Headband: Nylon plastic and #316 stainless; ratchet positioning

- Virtually indestructible, highly flexible, gooseneck boom. Rotates 300 degrees for left or right ear placement. Easy to adjust. Maintains its position for consistent voice quality.



- Available in single-ear and dual-ear styles.

